

High FREQUENCY VIBRATING TABLE VSB 70 duo



Vibrating table is designed for compacting concrete mixes in the test moulds. Thus made concrete sections are intended for further laboratory tests.

The device consists of a frame on which is placed over the rubber springs working vibrating plate. The bottom plate is fixed to the vibrating member with its own electric motor. Controlling the table is done by the electric control panel, located outside the machine, pedal /design NS/ or both elements. On the upper surface there is a rubber mat. Table is available in painted or galvanized finish.
 Option: mechanical clamping of moulds, triac speed control.

Technical data:		VSB 70 duo
Dimensions	A x B x H	330 x 880 x 300 mm
Table area		330 x 800 mm
RPM		9 500
RPM with triac control		100 to 9 500
Mass		55 kg
Input power		0,70 kW
Voltage		230 V / 50 Hz

Hi FREQUENCY VIBRATING TABLE VSB 70 duo REM



Vibrating table is designed for compacting concrete mixes in the test moulds. Thus made concrete sections are intended for further laboratory tests.

New version of classic table VSB 70 duo allows the use of electromagnetic clamping of moulds. Upper working surface of the sandwich structure has two built-in electromagnets and is covered by a protecting stainless steel sheet. The control panel can be placed on a table or hung on the wall.

The panel contains the following elements

- Main switch
- Timing relay
- Start and stop
- Selection of magnetic clamping AUT, 0 and MAN (aut. clamped when switched on, magnet. clamped off and on regardless of machine operation)
- Optional: triac speed controller

Technical data:		VSB 70 duo REM
Dimensions	A x B x H	330 x 880 x 270 mm
Table area		330 x 800 mm
RPM		9 500
RPM with triac control		1000 to 9 500
Mass		62 kg
Input power		0,85 kW
Voltage		230 V / 50 Hz