

Mixer for mortar and cement mashes Hobart**Three-speed mixer for mortar HOBART - N50.**

The norm mixer according DIN 1164, EN 196.

Three adjustable stirring speeds 140, 285, 591 RPM

Mixer including: Stainless steel mixing bowl - 5 liters

Flat agitator made of stainless steel

Flat aluminium stirrer

Protective cover

The possibility of retrofitting a programmer **OMH-4**. OMH 4 is pre-programmed and user-programmable automatic machine for switching up to 230V 50 Hz to the output of 700 W (inductive load - motors). Switching takes place in five optional programs, with the first test is always measuring the time: shows running time / space, the other two (three) are adjustable by the user, the last two / one are preset according to customer standards. Every time you turn the appliance machine beeps. Any program can be paused briefly pressing the Pause / Stop, long press then the program stops completely and the machine goes into mode of selection programs. OMH 4 can be operated placed on the desktop or mounted on a wall. OMH4 is also equipped with a sensitive thermal motor protection Hobart mixer.

OMH 4 in combination with 5 l Hobart does not automatically change the speed of mixer, gearbox is manually operated. Automat has a time delay for shifting of the desired degree.

Technical data:		Hobart N 50
Dimensions	A x B x H	380 x 264 x 435 mm
Voltage		230 V/ 50Hz
Input power		0,12 kW
Mass		21,5 kg.

For the same purposes, we also offer a Hobart mixer with a larger pot 10 and 20 liters.

